



Published by Product Quality Group - Marathon Petroleum Company LLC



TECHNEWS

MULTI-PURPOSE GEAR COMPOUND

PRODUCT

Multi-Purpose Extreme Pressure Gear Lubricant
Product Code: 571, 573

SAE Grades:

SAE 80W-90, SAE 85W-140

FEATURES

Extreme Pressure: Contains an extreme pressure additive to handle the high loads of gear systems.

Stable: Functions over a long period of time without breaking down.

Non-Foaming: Resists foaming to provide full-time lubrication.

Heat Resistant: Maintains its effectiveness under high-temperature conditions.

Performance Tested: Thoroughly tested in heavy-duty trucks, taxi cabs, fleet tests, chassis dynamometer and bench tests with excellent results.

Approved Product: Meets or exceeds the requirements for:

- API MT-1, GL-5, GL-4
- Ford M2C108C
- Mack GO-H and GO-J
- Military Specification MIL-PRF-2105E
- **Meets Requirements for Limited Slip Differentials**

APPLICATIONS

Any application where extreme pressure, multipurpose, hypoid GL-4, GL-5, MT-1 or MIL-PRF-2105E type lubricant is recommended. Typical applications include passenger car, truck and bus manual transmissions, differentials and final drives. Can also be used in some farm equipment special units and enclosed gear cases.

TYPICAL PROPERTIES		
SAE Grade	80W-90	85W-140
Gravity, °API	25.7	25.0
Viscosity, cSt@40°C	141	376
cSt@100°C	14.5	26.8
Viscosity Index	98	96
Pour Point, °C	-24	0